

Corner originally set as a post in 1820 by John Hendricks with the following witnesses: 12" sugar bearing north 13 degrees, thence west 12 links; and a 15" beech bearing south 48 degrees, thence west 12 links. (M.C.Atlas p. 15) A survey by O.W.Voorhies on November 23,1861 indicates no stone but the following witnesses: 5" swamp ash bearing north 7.50 degrees, thence east 42 links; and a 9" sugar bearing south 62.50 degrees, thence east 69.50 links.(Warren Legal Book p. 10) Corner referenced by Fleener on 11/14/59 and called a nail. Corner referenced by Burres on 8/14/63 and called a nail. Corner referenced by Day on 5/15/70 and called a nail. Corner referenced by Fortner on 3/19/75 and called a brass plug in steel box. Corner referenced by Wilcoxen on 10/8/96 and called a brass plug in steel box. Corner referenced by Whiteside on 8/12/01 and called a brass plug in steel box. Corner referenced by Whiteside on 8/12/01 and called a brass plug in steel box. Corner referenced by Whiteside on 8/12/01 and called a brass plug in steel box. Corner referenced by Whiteside on 8/12/01 and called a brass plug in steel box. Corner excavated on 10/21/03 and a brass plug was found 4" down. A #205 cast iron Harrison monument was set in position as the brass plug.

16052104		
REF.	DISTANCE	DESCRIPTION
li li	135.72'	Mag nail w/brass washer NW PwP#508-421 CB 60"up
2.	57.38'	PK nail N PwP#1-421 CB 60"up
3,	85.58'	Mag nail w/brass washer N PwP#23-421 CB 48"up
4.	77.50	Center steel corner fence post
<u> </u>		